



ES30 CE ANSI



RUBBER NOSEPIECE



INCLUDES STRAP



RUBBER TIPS

Built-in rubber nosepiece

Ventilated flexible temples with rubber temple tips

Includes black lanyard cord

Part No.

Black Frame with Cord

ES30CTM ●● AF Clear

ES30GTM ●● AF Gray



General Specifications

Weight: 27 gm
PD: 72 mm
Bridge: 14 mm
Lens base: 9 curve
Lens size diagonal: 78 mm
Lens size vertical: 46 mm
Lens thickness: 2.3 mm
Overall length (lens - tip): 103 mm
Overall width (hinge - hinge): 140 mm

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
5 or 6: Solar filter

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
K: Resistance to surface damage by fine particles
N: Filter with anti-fog
CE: Europe standard

Materials

Lens: polycarbonate
Temple: nylon
Frame: nylon
Screw: stainless steel
Nosepiece: rubber
Temple tips: rubber

Part No.

ES30CTM
ES30GTM

Lens Marking

2 - 1.2 P 1 F K N CE
5 - 3.1 P 1 F K N CE

Temple Marking

CE P EN166 F
CE P EN166 F



Temple Marking Symbols

Symbols

CE: Europe standard
P: Manufacturer's mark
EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact

